

SYSTEM AND METHOD FOR FABRICATING LOGIC DEVICES COMPRISING  
CARBON NANOTUBE TRANSISTORS

TECHNICAL FIELD OF THE INVENTION

This invention relates generally to logic devices and more specifically to a design, system, and method for fabricating logic devices comprising carbon nanotube molecular electronic devices.

BACKGROUND OF THE INVENTION

The U.S. semiconductor industry is facing increasingly difficult challenges as it moves into the production of features at sizes approaching 100 nanometers. The magnitude of some of these challenges has led to their being singled out as industry leaders as "grand challenges" requiring major initiatives to develop solutions using approaches with no historical precedent. Four of the six grand challenges identified in the National Technology Roadmap For Semiconductor include the ability to have affordable scaling, affordable lithography at and below 100 nanometers, new materials and structures, and gigahertz frequency operations on chips.

According to the technology roadmap for semiconductors, the minimum size of features will have to reach 130 nanometers by 2003 to keep pace with the continued doubling of the number of transistors on a chip every 18 months. After 2003, the roadmap indicates a lack of consensus about how to solve the fabrication challenges that lie beyond the 100 nanometer barrier. The problem confronting the industry is that the dominant technology used to make chips, optical lithography, used light to form patterns on silicon. Below 100 nanometers, the wavelength of light typically employed in chip production (193 nanometers and 157 nanometers) are too large to be useful. Several candidate technologies are currently vying for selection as successors to optical lithography. These include extreme ultraviolet lithography (EUV), an electron beam method called scalpel, and x-ray lithography. None has yet emerged as the preferred choice. Since it takes several years to bring the new technology up and running, the large

semiconductor manufacturers are becoming increasingly concerned about the time and capital investments that will be required to keep pace with the marketplace demands.

5           Therefore, it would be desirable to demonstrate the feasibility of fabricating carbon nanotube molecular electronic devices with a nanosize diameter (1-50 nanometers), micro-to-submicron size length (100 -1000 nanometers), and gate few nanometers long (1-5 nanometers).

10           It is widely recognized that the development of molecular electronics based on carbon nanotubes would enable logic devices to be built with billions of transistors and computers that are orders of magnitude more powerful than today's machines. Smart structures in salt grain size computers, for example, could be designed with integrated logic provided by 3-D array of molecular  
15           electronic devices. Further advances in wearable computers and other, as yet unforeseen, product possibilities will become more likely. Molecular electronics could also make possible information storage devices with immense capacity. For example, hard disks with storage capacities of terrabytes ( $10^{12}$  bytes) in small products the size of wristwatches with large storage capacities. Before these  
20           dreams become a reality, a way must be found to mass produce the molecular electronics devices. Scanning probe methods have proven feasible to fabricate single devices one atom at a time, but no way has yet been found to scale up the process. Chemically based self-assembly processes have also been suggested, but so far only the simplest structures have been built using this method. The  
25           problem of combining different materials and assembling molecular electronic devices with specific features remains a daunting challenge.

          Theoretical work by Chico et. al. (L. Chico, V. H. Crespi, L. X. Benedict, S. G. Louie, and M. L. Cohen, "Pure Carbon Nanoscale Devices: Nanotube  
30           Heterojunctions," Physical Review Letters, Vol. 76, No. 6, 5 February 1996) has suggested that introducing pentagon-heptagon pair defects into otherwise hexagonal nanotube structure may create junction between two topologically or electrically different nanotubes as bases for nanoscale nanotube devices. Saito

(S. Saito, "Carbon Nanotubes for Next Generation Electronic Devices," Science, Vol. 278, 3 October 1997) describes possible theoretical designs of a carbon nanotube that may function as molecular electronic devices. Those and other similar theoretical works outline the possibility to use carbon nanotubes as molecular devices but fail to propose a design of such device and a method of its fabrication.

Collins et. al. (P. Collins, H. Bando, A. Zettl, "Nanoscale Electronic Devices on Carbon Nanotubes," Fifth Foresight Conference on Molecular Nanotechnology) have experimentally demonstrated the rectification properties of single-wall carbon nanotubes. This work also fails to propose a design of carbon nanotube molecular electronic device and a method of its fabrication.

Suenaga et. al. (K. Suenaga, C. Colliex, N. Demoncy, A. Loiseau, H. Pascard, F. Willaime, "Synthesis of Nanoparticles and nanotubes with Well-Separated Layers of Boron Nitride and Carbon," Science, Vol. 278, 1997) have reported an effort to fabricate nanoscale electronic devices by fabricating concentric nanotubes out of carbon and boron nitride. This concentric design is achieved by filling-in already synthesized carbon nanotube. This design concept may work for a two-terminal device such as diode but cannot be scaled to function as a three-terminal device such as transistor. This work has also failed to explain how such device would function and has not addressed the interconnect problem.

M. Terrones et. al. (M. Terrones et. al., "Controlled production of aligned-nanotube bundles," Letters to Nature, Vol 388, July 1997) reported on efforts to fabricate horizontally aligned carbon nanotubes that may be used as electronic devices. This effort fails to describe any design of a carbon nanotube molecular device.

Most recent designs of carbon nanotube based molecular electronic devices, such as Dekker et. al. (Tans SJ, Verschueren ARM, Dekker C, "Room-temperature transistor based on a single carbon nanotube," Nature 393: (6680)

49-52, May 7, 1998), consist of a carbon nanotube spanned over two, three, or more metal electrodes. Such device may indeed function as a diode or a transistor but it cannot be scaled and cannot be connected to yet another carbon nanotube transistor.

5

Most recently Hu et. al. (J. Hu, M. Ouyang, P. Yang, and C. Lieber, "Controlled growth and electrical properties of heterojunctions of carbon nanotubes and silicon nanowires," Nature, Vol. 399, May 1999) has demonstrated nanoscale electronic device made of joined Si nanowire and carbon nanotube. Although successful, this nano-devices cannot be scaled up and therefore cannot be practically fabricated in a large-scale manufacturing operation.

10

None of the state-of-the-art research has addressed the scalability of fabricating carbon nanotube based molecular electronic devices, their interconnection, and interconnection between the molecular logic device and the outside world.

15

Most recently Li et. al. (J. Li, C. Papadopoulos, University of Toronto; J. Xu, Brown University, "Growing Y-junction carbon nanotubes," Nature, Vol 402, 18 Nov. 1999, pp. 253) has used nanostructured template channels to grow Y-junction carbon nanotube heterostructures from nanochannel alumina template. They first created the top pores with one voltage and then reduced it midway through the electrochemical formation of the pores. They observed that the voltage is proportional to number of pores, therefore, twice as many appeared, most branching from the original pore. This creates Y template. Catalyst was deposited electrochemically at the bottom of the template channels from which carbon nanotubes were grown. Top CNTs were close to twice the diameter of the two bottom branches. They observed that the length of the pores depends on the thickness of the substrate and the length of the Y junction depends on the timing of the current alteration. The method described in this work only addresses formation of large number of evenly distributed templates without control over pattern of the template. Use of template with variable shape to

20

25

30

create carbon nanotube that conforms that shape and the method of producing the variable template has been disclosed in U.S. Patent No. 6,146,227, on page 5, line 43, entitled "Method for Manufacturing Carbon Nanotubes as Functional Elements of MEMS Devices" which is incorporated herein by reference. The present patent is a continuation-in-part of that issued patent.

The present invention solves all of the above problems that were not addressed by current research. The present invention identifies several designs of carbon nanotube electronic devices made of individual vertically aligned carbon nanotubes embedded in a silicon or aluminum substrate. The advantage of this design is that it is flexible and is suitable for fabrication of two-terminal (diodes) and three-terminal (transistors) carbon nanotube electronic devices, and more complex logic devices made of plurality of carbon nanotube diodes and transistors. Another advantage of the design is that offers true 3-D architecture. Another advantage of the design is that it includes interconnects between the carbon nanotube devices and interconnects with the outside world.

The advantage of the fabrication process is that it can produce patterns of vertically grown carbon nanotubes with control over the location, dimension, and electric properties of the carbon nanotube. Another advantage of the fabrication process is that it can be scaled to produce large number of devices with a batch process. Another advantage of the fabrication process is that it can also fabricate the interconnects. Another advantage of the fabrication process is that vertical growth permits high-density packing of devices. The fabrication technology will enable device densities of  $10^{12}$  per  $\text{cm}^2$  (for 3 vertically stacked devices) limited only by lateral interconnect technology (among the carbon nanotubes) and the number of vertically stacked devices. With the help of lateral carbon nanotube interconnects, the technology could provide device densities to  $10^{14}$  per  $\text{cm}^2$ . Further vertical stacking of the devices would enable magnitudes more of device densities.

The carbon nanotube devices of this invention and their fabrication process are suitable for large-scale manufacturing and interconnection of

5 molecular electronic devices in a "salt-grain" size integrated circuit. This large-scale, low-cost approach will provide extremely fast, low-power, ultra-high-density logic and memory devices which operate at room temperature. The resulting product possibilities include fast, multi-gigaflop processors, smart structures, wearable computers, random access memories with terabyte ( $10^{14}$  bytes) capacities, and other exciting new market opportunities.

11/11/2010 10:11:11 AM

SUMMARY OF THE INVENTION

One or more of the problems outlined above may be solved by the invention of the present disclosure. The disclosure describes designs of carbon nanotube molecular devices and integrated processes for manufacturing and interconnecting a 3-D architecture of molecular devices made of carbon nanotubes, suitable for large-scale manufacturing. This large-scale, low-cost approach may provide extremely fast, low-power, ultra-high-density logic and memory devices which operate at room temperature.

In one embodiment, a logic device comprises a plurality of interconnecting carbon nanotube devices, wherein the interconnecting carbon nanotube devices comprise a plurality of electrically connected carbon nanotubes on one or differing vertical levels, and wherein the carbon nanotubes are formed within at least one nanosized catalyst retaining structure.

In another embodiment, a method of fabricating a carbon nanotube device comprises the steps of fabricating a template of nanosized catalyst retaining structures within a substrate, depositing catalyst within the nanosized catalyst retaining structures, and synthesizing carbon nanotubes that conform to the template of the nanosized catalyst retaining structures.

In another embodiment, a method for manufacturing an array of transistors comprises growing aligned carbon nanotubes within a catalyst retaining template, and introducing at least one discontinuity within a structure of the carbon nanotubes, wherein the discontinuity is a conductivity discontinuity along a vertical axis of the carbon nanotubes, wherein if one discontinuity is introduced a diode is formed and if two discontinuities is introduced a transistor is formed.

In another embodiment, a carbon nanotube transistor comprises a carbon nanotube with at least two defects therein, and wherein the defects divide the carbon nanotube into three regions with differing conductivities.

5 In another embodiment, a logic device comprises a substrate, a layer of insulating material in which at least one catalyst retaining structure is formed, at least one carbon nanotube formed within the catalyst retaining structure, wherein the carbon nanotube has at least two defects therein, and wherein the defects divide the carbon nanotube into at least three regions with differing conductivities.

10 It should be noted that many other embodiments may be apparent from this disclosure, and that such embodiments are intended to be included within the scope of the claims appended below.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200



BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following description taken in conjunction with the accompanying drawings in which like reference numerals indicate like features and wherein:

FIGURE 1 shows two of many possible configurations for carbon nanotube molecular electronic devices. The structural defects (pentagon-heptagon pairs) produce a discontinuity in conductivity, believed to be the origin of the experimentally observed rectifying behavior;

FIGURE 2 shows schematic representation of a portion of a carbon nanotube molecular electronic device architecture, including vertical metallic nanotube interconnects and horizontal metallic film interconnects;

FIGURE 3 shows carbon nanotube molecular electronic device fabrication process steps;

FIGURE 4 shows the set-up for controllable electrochemical etching of the template location, diameter, shape and length;

FIGURE 5 shows the results of electrochemical etching as function of different current fluxes;

FIGURE 6 shows an example of template discontinuities possible with electrochemical etching controlled by varying the current flux as function of time;

FIGURE 7 shows an example of template discontinuities possible with electrochemical etching controlled by spacing of the templates, doping concentration, and varying the current flux as function of time;

FIGURE 8 shows method for establishing direct lateral connection between adjacent carbon nanotubes by sufficiently expanding nanotubes' diameters;

5           FIGURE 9 shows control of the discontinuity of the template with the help of continuous doping concentration profile of the substrate along its depth;

FIGURE 10 shows control of the discontinuity of the template with the help of discrete doping concentration profile of the substrate along its depth;

10

FIGURE 11 shows control of the discontinuity of the template with the help of discrete bricks of different doping concentration;

FIGURE 12 shows individual control of fabricating each template or group of templates with the help of individual electrode for each template or group or group of templates;

15

FIGURE 13 shows individual control of fabricating each template or group of templates with the help of masking.

DETAILED DESCRIPTION OF THE INVENTION

Preferred embodiments of the present invention are illustrated in the  
FIGURES, like numerals being used to refer to like and corresponding parts of  
the various drawings.

Figure 1 illustrates two possible configurations of carbon nanotube  
molecular electronic devices. The structural defects 32 -35, as illustrated in  
Figure 1, are pentagon-heptagon pairs which produce a discontinuity in  
conductivity. By fabricating vertically aligned carbon nanotube transistors with  
the fabrication technology disclosed in this application and related U.S. patent  
application Serial No. 09/669,212 entitled "Method for Manufacturing Carbon  
Nanotubes as Functional Elements of MEMS Devices" filed on May 11, 2000,  
which is incorporated herein by reference, enables device densities of  $10^{12}$  per  
 $\text{cm}^2$  limited only by lateral interconnect technology among the carbon nanotubes.  
Another interconnect technology may make it possible to provide device densities  
of  $10^{14}$  devices per  $\text{cm}^2$ . The production of multiple carbon nanotube transistors  
along the vertical axis of a single carbon nanotube is also an entirely new idea.

Figure 2 illustrates complex devices in a 3-D architecture of carbon  
nanotube molecular electronic devices. It is possible with the innovative  
fabrication method to manufacture an array of electronic devices made of carbon  
nanotubes. The illustration shown in Figure 2 provides a stack of vertically  
stacked electronic devices with a first electronic device 10 and a second  
electronic device 12 stacked under first electronic device 10. Electronic device 10  
comprises a plurality of vertically aligned carbon nanotubes 14 that are grown  
from a first contact plane 16. The vertically aligned carbon nanotubes 14 are  
grown within vertically aligned holes within a substrate material. A contact plane  
20 is provided allowing conducting interconnects 22 to contact the gates 24 of  
vertical carbon nanotube transistors 14. A second layer of substrate material  
surrounds the upper portion of the carbon nanotube transistors 14, ending in an  
upper contact plane 28 with bond pads 30 allowing the transistors or other logic  
devices within the device to be accessed from the outside world. A single carbon

nanotube segment 14 will have two defects which divide the carbon nanotube 14 into three different conducting regions 36, 38 and 40 along the length of the nanotube. Altering the conductivity at many points along the nanotube axis also allows one to build multiple stacked transistors on a single carbon nanotube of the array, thus offering a 3-D architecture as illustrated by the transistor device 12 stacked beneath electronic device 10. The interconnection of carbon nanotube transistors in a given layer, or as stacked on carbon nanotube, can constitute a logic device.

The proposed carbon nanotube device fabrication process consists generally of the following process steps, which are illustrated in Figure 3: the generation of a template, such as the etched cavity 50, within a substrate material 52 or other like structure; the deposition of a catalyst 54 along the inner walls of the etched cavity 50, which is then followed by the carbon nanotube growth or synthesis of carbon nanotube 56, which is molded to conform to the etched cavity 50. Electrical contacts (interconnects) 57 may be fabricated at various places along the vertical axis of the carbon nanotube 56. It is possible to generate an array of template holes or etched cavities 50 by using an electrochemical etching on a selected substrate such as silicon or aluminum.

An example of the electrochemical setup is shown in Figure 4, wherein an array of etched templates 58 with controlled discontinuity 60 is formed within a substrate 62. It is possible, in some embodiments of the present invention, that pits 63 are pre-etched for patterning the etched templates. Depending on the desired outcome and the variation in the process parameters (primarily the etching current), the diameter of the generated template holes 50 will be between 1 nanometer and 50 nanometers. The length of the holes will equal the thickness of substrate 62. This may be on the order of one micron for a nanotube which only has a few carbon nanotube transistors along its length, to tens of microns as the 3-D nature is scaled up. For example, several carbon nanotube electronic devices are formed along the length of a nanotube by dynamically controlling the diameter of the template by controlling the current flux applied through an electrode placed on one side of the substrate. Furthermore, it will be possible to

generate carbon nanotubes with different conducting properties by precisely controlling the current flux so as to produce template segments with different diameters along the vertical axis, as illustrated in Figure 5.

5           Figure 5 illustrates the process of forming a discontinuity in the template along its length with snap-shots at different times. It can be seen that at different times a different etch current is applied to form the template discontinuity. During the first time interval the current has been kept constant and that produced the uniform template segment 64. At second time interval the current was increased  
10 as to produce a template segment 66. At third time interval the current was reduce to its original level and kept there. This produced the third segment 68.

          Figures 6 and 7 show examples of template discontinuities possible with electrochemical etching. Preferred discontinuities comprise variations in the  
15 diameters of the templates along their lengths, producing serial segments with different diameters. An alternative way to produce discontinuities is to divide or branch the templates along their lengths, producing parallel segments with different diameters. The basic designs of CNMEDs that are possible with variable templates include diodes, transistors, and other two, three, and multi-terminal  
20 electronic devices. For any template that can be fabricated, a corresponding carbon nanotube can also be fabricated. A number of other designs can be fabricated that take advantage of the complex types of templates that are described here.

25           Figures 9, 10, and 11 show a method to control the discontinuity of the template by manipulating the doping concentration of the substrate and its distribution. This approach represents an effort to balance the fabrication process as to make the critical process rely on established semiconductor processes. This may lead to making the process more manufacturable and reproducible.  
30 Standard established semiconductor processes can deliver precise doses of doping over specified depths. Thin film deposition of silicon is another standard semiconductor process. When doping concentrations are controlled, the

electrochemical process only needs to provide a constant current flux and the doping difference will produce the desired template shapes.

Figure 8 illustrates a method for establishing a direct lateral connection between adjacent carbon nanotubes. Such fundamentally new interconnect approaches would obviate the need for conventional lithographed metallic interconnects which limit the lateral spacing of the carbon nanotube devices. With the help of direct carbon nanotube interconnects, the technology could provide device densities to  $10^{14}$  per  $\text{cm}^2$ . Furthermore, the ohmic contact between carbon nanotube and metal, which may be a limiting factor in the performance of the carbon nanotube devices, is replaced by nanotube-nanotube contact that is more intrinsic. Contact-less interconnection by electron tunneling or spin coupling shifts the entire paradigm of the molecular electronic device.

Figure 12 shows individual control in the fabrication of each template or group of templates with the help of individual electrodes for each template or group of templates. This approach allows different currents to be provided to different electrodes and thereby allows micro-management of the electrochemical process.

Figure 13 shows individual control of fabricating each template or group of templates with the help of masking. With this method pattern of a mask is applied to the substrate, covering an area of the substrate and exposing the rest of the substrate. An electrochemical etching can be applied to produce a template or a group of templates with desired discontinuities, over the exposed area. This approach allows that templates with different types of discontinuities be produces at different locations on the substrate.

The present invention builds on the fabrication technology disclosed in U.S. patent application Serial No. 6,146,227 entitled "Method for Manufacturing Carbon Nanotubes as Functional Elements of MEMS Devices" which is incorporated herein by reference. The referenced patent discloses method of fabricating a nanosize catalyst retaining structure (NCRS) with precise dimensions and location that can serve as a template for a carbon nanotube with

controllable orientation, diameter, location, length and shape. The carbon nanotube is synthesized by thermal deposition of hydrocarbides directly from within the template coated with catalyst. The present disclosure describes in detail the methods of changing the shape of the template and with that the shape of the synthesized carbon nanotube. The change of the carbon nanotube shape introduces controlled discontinuities in the structure of the carbon nanotube. The discontinuities in the structure of the carbon nanotube promote electronic functions that enable the design of carbon nanotube based molecular electronic devices. The present disclosure also describes designs of molecular electronic devices that can be fabricated with the template method. The present disclosure also describes methods of interconnecting the carbon nanotubes.

The present fabrication process solves the problem of introducing manufacturable controllable discontinuities along the length of a carbon nanotube. It makes sense to talk only about discontinuities along the length of the nanotube since the nanotubes are essentially one-dimensional structures with their lengths many times the sizes of their diameters. The present process claims the use of a template to shape the carbon nanotube along its length. Existing methods rely on junctions between nanotubes and on kinks in their structure to produce nanotube electronic devices.

The present fabrication process solves the problem of fabricating the nanotube devices in an integrated process instead of fabricating them separately and then assembling them. The present process involves a fabrication method that produces the carbon nanotubes in-place, embedded within the substrate. This is achieved by using templates which are embedded in the substrate and consequently producing carbon nanotubes that are also embedded in the substrate. The integrated process can also produce the interconnects among the individual carbon nanotube devices. Existing methods rely on fabricating the nanotubes separately and then placing them one-by-one on electrodes to produce nanotube electronic devices. Alternatively, they may rely on random dispersion of the nanotubes over the electrodes.

The present fabrication process solves the problem of scalable manufacturing process for production of functional carbon nanotube electronic devices. The innovative process claims fabrication method that produces an array of functional carbon nanotube electronic devices in a single process. This is achieved by fabricating an array of templates that are precisely patterned on the substrate. In turn, the array of templates is used to produce an array of carbon nanotube devices. Existing methods rely on individually fabricated carbon nanotube devices that need to be interconnected to form a functional device. Some existing methods can also produce an array of uniformly distributed carbon nanotubes but cannot fabricate individual precisely-located nanotube or a pattern of nanotubes that are also functional.

The present fabrication process solves the problem of interconnects among the individual carbon nanotube devices and an interconnect to an external world. The present process involves fabrication of horizontal and vertical interconnects as part of the integrated fabrication process. Horizontal interconnecting is achieved by patterning metal interconnect lines in a plane sandwiched between substrate layers, combined with fabricating vertical nanotubes that pass through the metal interconnects. Alternative horizontal interconnects are achieved with the help of horizontal carbon nanotubes. Alternative horizontal interconnects are achieved by expanding the carbon nanotubes' diameters until two adjacent nanotubes touch. Vertical interconnects are achieved with the help of vertical conductive carbon nanotubes and by stacking one carbon nanotube device on top of another. Existing methods of interconnecting carbon nanotube devices rely on external contacts or on interconnects that are fabricated separately from the nanotubes. There are no existing vertical interconnect technologies.

The innovative carbon nanotube electronic device design solves the problem of existence of carbon nanotube logic devices that are molded within a substrate and not free-formed, that can be connected to other carbon nanotubes laterally or vertically, and that can form a complex 3-D architecture. This is achieved with the above mentioned innovative fabrication process. Existing



carbon nanotube electronic device designs are free-formed, cannot be easily connected to other nanotubes, and are two terminal electronic devices (diodes).

5 The present disclosure illustrates: 1) a method of fabricating basic carbon nanotube molecular electronic devices (CNMEDs), 2) a method of fabricating complex devices in a 3-D architecture of CNMEDs, 3) basic designs of (CNMEDs) possible with the present fabrication methods, and 4) complex devices in a 3-D architecture of CNMEDs possible with the present fabrication methods.

### 10 **Fabrication process**

The method of fabricating the basic CNMEDs and the complex devices in a 3-D architecture of CNMEDs is a unique combination of controlled electrochemical etching and catalytic carbon nanotube growth technologies. This fabrication takes advantage of the benefits offered by the established electrochemical etching technology with the emerging technology of carbon nanotube synthesis. The innovative fabrication process produces a 3-D pattern of carbon nanotubes synthesized by thermal deposition of hydrocarbides directly from within a 3-D template coated with catalyst.

20 The present fabrication process enables introducing controlled discontinuities in a template and, with that, in the structure of the carbon nanotubes. Preferably, the discontinuities will be introduced by exploiting the process of controlled electrochemical etching to vary the template diameter and shape along its length. The introduction of controlled discontinuities in the structure of the carbon nanotubes alters the bond configuration, and therefore the conductivity properties, at various points along the vertical axis of the nanotube. Figure 1 shows an example of a carbon nanotube resulting from such process.

### 30 **Innovative basic CNMEDs and complex devices in a 3-D architecture of CNMEDs**

This invention defines CNMEDs as electronic devices that exhibit electronic functions such as rectification, switching, and emission. CNMEDs that

are possible with the innovative fabrication method include diodes, transistors, and other two, three, and multi-terminal electronic devices (such as stacked transistors and diodes). The introduction of controlled discontinuities in the structure of the carbon nanotubes enables the functionality of the CNMED devices. Introduction of integrated interconnects that connect two or more carbon nanotubes in a device able to execute a logic operation also enables the functionality of the CNMEDs. Introduction of vertical stacking of two or more carbon nanotube devices also enables the functionality of the CNMEDs. Figure 2 shows schematic representation of a portion of CNMED architecture, including vertical metallic nanotube interconnects and horizontal metallic film interconnects.

#### **Fabrication process steps**

The present carbon nanotube device fabrication process consists of the following process steps: (1) generation of template, (2) catalyst deposition, and (3) nanotube synthesis, as shown in Figure 3. Other optional steps can be added to augment the fabrication process.

#### **Control of the carbon nanotube pattern in horizontal plane**

The in-plane horizontal pattern of the templates or groups of templates can be used to control the pattern of the CNMEDs. For example, depending on the desired interconnections (i.e., depending on the particular logic gates desired), the entire process can be designed so that uniform templates (which will generate the vertical metallic interconnects) and non-uniform templates (which will generate CNMEDs) are grouped in small blocks of arrays. Metal interconnects are then used to connect the CNMEDs with the vertical metallic interconnects to create the more complex logic devices.

Control over template patterns is achieved by using means to initiate the etching at desired locations. One way of achieving this initiation is to pattern the substrate with a mask to generate pits at precise locations on a substrate that will initiate formation of a template. Another way of initiating the formation of the holes is to place an impurity, local defect, stress, or optical energy as method to initiate the formation of a template. The impurity, local defect, stress, or optical

energy can be placed using masking techniques or by direct write/deposit methods. A self-organizing patterning that produces a pattern of impurity, local defect, stress, or optical energy may also be used to initiate the electrochemical etching.

5

### **Carbon nanotube interconnects**

The present fabrication process includes means of interconnecting the carbon nanotube devices in horizontal and vertical planes to achieve true 3-D capable interconnection. Horizontal interconnecting can be achieved with  
10 patterned metal interconnect lines that intersect with the vertical nanotubes. Vertical interconnects can be achieved with the help of vertical conductive carbon nanotubes and by stacking one carbon nanotube device on top of another. The three dimensional architecture of CNMEDs, illustrated in Figure 2, is interconnected with a combination of horizontally patterned metal lines (using  
15 conventional lithography) and integral vertical carbon nanotube interconnects, consisting of carbon nanotubes that conduct all the way or part of the way along their vertical axes.

20

25

30

Horizontal interconnection is achieved by building a layered structure of doped silicon and patterned metal interconnects with interconnect pads that are strategically positioned to make sure they will interconnect with the vertically etched templates. Only the top layer of the structure is patterned to produce the horizontal pattern of the templates. Once the formation of the template is initiated, the entire template will be etched through all the layers of doped silicon and metal film. At designed locations, the vertically grown carbon nanotubes will intersect the horizontal interconnects and, in particular, the strategically positioned metal pads. The doped silicon layers also act as spacing layers with predefined vertical spacing to allow connection between the conducting, semiconducting, and nonconducting vertical segments of the carbon nanotubes. The metal lines will be used to control the functioning of the electronic devices for input, output, and addressing of the logic devices. Complex logic devices can be constructed by strategically interconnecting two or more carbon nanotubes on the same or different vertical levels.

Vertical interconnection is achieved with the help of conductive carbon nanotubes whose entire purpose is to provide vertical interconnection. These interconnect carbon nanotubes are synthesized with the help of a cylindrical template with constant diameter. It is preferred that all templates with uniform diameter and all templates with variable diameter be synthesized on separate locations of the device away from each others so as to better control the template production. Another method of achieving vertical interconnection is to stack one carbon nanotube device on top of another from a single template.

Interconnection with the outside world may be achieved by funneling all the required internal connectors via conducting carbon nanotubes to a top level substrate where metallic bond pads are lithographically fabricated. Bonding of gold contact pads to a carbon nanotube has already been demonstrated by Haesendonck et. al. (C. Van Haesendonck, L. Stockman, R. Vullers, Y. Bruynseraede, L. Langer, V. Bayot, E. Grivei, J. Issi, J. Heremans, C. Olk, "Nanowire bonding with the scanning tunnelling microscope," Surface Science 386 (1997), 279-289). A ball grid array type of connection can then easily be achieved to connect the molecular device with the outside world.

#### **Substrate for CNMEDs**

Doped silicon is the preferred substrate material. This includes lightly and heavily doped P and N type silicon. It is preferred that the doping is introduced while the silicon crystal is grown in order to produce uniform concentration of doping along the thickness of the substrate. For thin silicon layers, the doping can be introduced by ion implantation.

Alternatively, aluminum is the next preferred substrate. The purity of the starting aluminum is important factor for electrochemical etching of templates. Other substrate choices include materials or composites that are suitable for electrochemical etching. A gallium arsenide substrate is also acceptable as substrate for electrochemical etching of templates.

To achieve the 3-D architecture described above, the substrate has to be prefabricated to include the metal interconnects. A prefabricated substrate includes a layered structure of doped silicon and patterned metal interconnects. Masking oxide or nitride layers will be used to produce the patterned metal lines.

5 The most common interconnect materials include metals such as aluminum, copper, tungsten, titanium, nickel, chromium and various metal alloys. The silicon layer may be epitaxially grown, or it may be deposited. Any silicon, including amorphous, polysilicon, or crystalline silicon is acceptable as a substrate for electrochemical etching of templates. It is preferred that the substrate be made

10 of crystalline silicon. Acceptable ways of producing the crystalline silicon include depositing polysilicon over the metal layer, implanting it with the right dose of dopants, and recrystallizing it over in a high temperature baking process. Alternatively, the desired substrate can be bonded together.

15 A prefabricated aluminum substrate would include layers of aluminum and patterned metal interconnects. The desired substrate can be fabricated by subsequent stacking of deposited metal lines and deposited aluminum that may have to be recrystallized.

## 20 **Electrochemical etching process**

The preferred embodiment of the present device fabrication process relies on electrochemical and photoelectrochemical etching as a mechanism of generating the template. The methods of controlling an electrochemical etching process of N-type silicon are described in detail by Lehmann et. al. (V. Lehmann

25 and H. Foll, "Formation Mechanism and Properties of Electrochemically Etched Trenches in n-Type Silicon," J. Electrochem. Soc., Vol. 137, No. 2, February 1990) which is incorporated herein by reference. The teachings of Lehmann also apply to P-type silicon, with minor adjustments known to those skilled in the art. Other research (G. Bomchil, A. Halimaoui, I. Sagnes, P. Badoz, I. Berbezier, P.

30 Perret, B. Lambert, G. Vincent, L. Garchery, J. Regolini, "Porous silicon: material properties, visible photo- and electroluminescence," Applied Surface Science 65/66, 1993, pp. 394-407; H. Ohji, S. Lahteenmaki, P. French, "Macro porous silicon formation for micromachining," Proc. SPIE-Int. Soc. Opt. Eng., 3223, 1997,

pp. 189-197) describes porous silicon formation and its use with patterning for micromachining.

An example of electrochemical set-up of this invention is shown in Figure 4. In one such example of electrochemical etching P++, P+, N-, and N-- doped silicon can be etched with a diluted HF acid (25% HF, 25% de-ionized water, 50% ethanol) and current densities of 10 mA/ cm<sup>2</sup>.

Electrochemical etching of a layered substrate of silicon and metal film is slightly different from electrochemical etching of single layer of silicon. After the template reaches the depth where the metal layer exists, the etchant will simply dissolve the thin metal layer and will continue with the etching of the silicon. This process can be used to monitor the current load and to determine when the etching of the silicon has reached the metal layer. This information may be used for control purposes. After the metal has been dissolved, there will still be a ring of metal on the circumference of the template.

After the template has been fabricated, one can optionally bake the sample in oxygen environment as to oxidize the walls of the template and electrically isolate the template walls from the surrounding substrate. This process will disable or reduce any current leakage from one nanotube (that will be synthesized within the template) to an adjacent one. This oxidation process will also shrink the diameter of the template as oxygen atoms bond to silicon atoms. Alternatively, the template walls can be baked in nitrogen atmosphere to create a nitride wall. Any other reduction of the surface with another gas may also be implemented to achieve similar goals.

#### **Control of the carbon nanotube discontinuities**

The discontinuities of the template along the vertical axis of the template are used to control the bond configuration, and therefore the conductivity properties, at various points along the vertical axis of the nanotube. Preferably, the discontinuities will be introduced by exploiting the process of controlled electrochemical etching to vary the template holes along their lengths. The

preferred means for achieving discontinuities is to vary the diameters of the templates along their lengths, producing serial segments with different diameters. An alternative way to produce discontinuities is to divide or branch the templates along their lengths, producing parallel segments with different diameters.

5

Control of the electrochemical etching process is the most critical step in the preferred embodiment of the present fabrication process. Variation of the process parameters, such as the current density, the concentration of the etchant, the doping of the silicon substrate, the luminescence, the crystal  
10 orientation of the substrate, and the adjacent template spacing can be used to control the template discontinuities and to thereby generate carbon nanotubes with different conducting properties.

Dynamic control of the diameters of the templates along their depth is achieved by controlling the process parameters as a direct function of the depth of penetration of the etchant, and an indirect function of the etching rate and the etching time. In the preferred embodiment, the current flux is precisely controlled as function of time so as to produce template segments with different diameters along the vertical axis (Figure 5). In one example, the electrochemical etching  
15 takes 10 minutes, where during the first 4 minutes, the current density is held at constant 3 mA/cm<sup>2</sup>, followed by 2 minute etching at 10 mA/cm<sup>2</sup>, followed by 4 minute etching at 3 mA/cm<sup>2</sup>. It is assumed that the doping concentration is constant over the thickness of the substrate. The resulting template will be a cylindrical template with a bulge in the middle (Figure 6A). If the order of the  
20 current density is switched, the resulting template will be an hour-glass shaped template (Figure 6B). Examples of other possible discontinuities resulting from variations in the current flux as function of time are shown in Figures 6C-E. In Figure 6C, the process of Figure 6A is repeated two times. In Figure 6D, the current density has been increased, but it has not been decreased. In Figure 6E,  
25 the current density is increased with a constant rate to produce template with tapered walls. Any other combination of the above examples is also possible with the present process.  
30

In another embodiment, the adjacent template spacing, which is produced by patterning the initiation location and spacing of the template, can be used as a controlling parameter in conjunction with the doping concentration of the substrate. If the template spacing is too far in relation to the doping density, the templates will divide, as illustrated in Figure 7A, or branch, as shown in Figure 7B. If the reverse is true, the template will join. Precisely controlling the current flux as function of time (indirectly as function of the depth of penetration) can produce a template that divides or branches in a desirable fashion along the vertical axis, effectively producing parallel template segments with different diameters. Figure 7C illustrates more complex templates that can be produced with this process. Any other combination of the above examples is also possible with the present process.

The methods to control the discontinuity of the template and therefore the discontinuity of the carbon nanotube are also applicable to an aluminum substrate. The current density, the concentration of the etchant, and the adjacent template spacing are suitable process parameters that can be used to control the template discontinuities and thereby generate carbon nanotubes with different conducting properties. Substrate doping, luminescence, and the crystal orientation are not applicable process parameters in etching an aluminum substrate.

Many different templates can be fabricated with the electrochemical etching technology described above for use as templates to fabricate carbon nanotubes. These variations are contemplated to be within the skill of a person of ordinary skill in the art and are therefore believed to be within the scope of this disclosure and the appended claims.

#### **Control of the carbon nanotube diameter and length**

Process parameters, such as the current density, the concentration of the etchant, the doping of the silicon substrate, the luminescence, the crystal orientation of the substrate, and the adjacent template spacing all influence the diameter of the initiated template. Depending on the size of the desired



electronic device, it is preferred that the diameter of generated template holes be between 1 and 50 nm. The electrochemical etching is also capable of generating templates that are up to microns in size. The length of the holes can be controlled by timing the entire process and may equal the thickness of the substrate. This may be on the order of one micron for a nanotube which has only one or few CNTs along its length, to tens of microns as the 3-D nature is scaled up (i.e., tens of CNTs along the length of a nanotube).

### **Catalyst deposition in the templates**

The catalyst deposited within an etched cavity or template shape may be a metal catalyst, such as iron, nickel, copper, or other like catalysts known to those skilled in the art,

After the template is formed, it is coated with a metal catalyst (Fe, Ni, Co, etc.). This can be achieved by chemical deposition (G. Che, B. Lakshimi, C. Martin, E. Fisher, "Chemical Vapor Deposition Based Synthesis of Carbon Nanotubes and Nanofibers Using a Template Method," Chem. Mater., 10, '98) or electrodeposition (A. Bard, L. Faulkner, Electrochemical Methods: Fundamentals and Applications, John Wiley & Sons, 1980, p. 372). Such techniques have already been demonstrated. For the case of electro-oxidation and electrodeposition, we may utilize the same electrical contacts as those used for the electrochemical etching. The main challenge in this step is the uniform deposition or formation of catalysts within the template. It is desirable that the template be kept wet before proceeding with the catalyst deposition, as drying of the template walls creates surface tension that makes the catalyst diffusion more difficult. For templates with more complex shape, the diffusion of the catalyst molecules within the network of templates will be slower. A DOE can be conducted to determine the timing required to diffuse the catalyst penetration. Mechanical vibration, vacuum suction, temperature, and use of surfactants may be employed to improve the diffusion process.

Alternatively, the deposition of the metal catalyst can be done concurrently with the electrochemical etching by incorporating traces of the metal

catalyst in the etch solution. For example, iron salt may be added to the HF concentration mentioned above to introduce the catalytic metal into the etch solution. As the electrochemical etching proceeds, the metal catalyst will concurrently be deposited on the walls of the template. One advantage of this method of catalyst deposition is that it is not affected by the complexity of the template network since it is distributed concurrently with the etchant. This is the preferred method of catalyst deposition within the template.

### Carbon nanotube synthesis

Due to the location of the catalyst, carbon nanotubes grow and are encased by the walls of the hole, causing carbon nanotubes to grow radially inwards. The diameter of the nanotube is also confined by the inner walls of the hole. Thermal deposition of hydrocarbides or CVD processes can be used to grow carbon nanotubes within the templates. In this process, a nanotube's thickness is controlled by timing the CVD process and terminating it as needed. A carefully designed process may lead to a synthesis of single wall carbon nanotubes. Alternatively, multi-walled carbon nanotubes may also be generated.

The challenge here is to achieve adequate quality of the generated carbon nanotubes, namely their conductivity profile and purity of the carbon nanotube bond. The generated carbon nanotubes will take the shape of the templates where they are synthesized. A template with variable diameters along its length will produce carbon nanotubes with variable diameters along their lengths. A template with divided or branched legs will produce carbon nanotubes with divided or branched legs. The appropriate change in the diameter of the carbon nanotube induces the desired change in the conductive properties of the carbon nanotube. For example, slightly constricting a metallic nanotube induces a pentagon-heptagon defect, resulting in a semiconducting segment of a nanotube (Figure 1). The use of a template to mold and bound the shape of the carbon nanotube is unique.

After the carbon nanotube is synthesized in a layered structure of silicon and metal, the nanotube will make contact with the metal ring which is left after

etching away the template through the metal film, thereby establishing metal contact. Thermal heating or electrical load may have to be applied to diffuse the metal layer with the carbon nanotube and to establish good electrical contact.

5      **Carbon nanotube molecular electronic devices**

10      The basic designs of CNMEDs that are possible with the innovative fabrication method include diodes, transistors, and other two, three, and multi-terminal electronic devices (such as stacked transistors and diodes). A number of other designs can be fabricated that take advantage of the complex types of templates that are described above. For any template that can be fabricated, a corresponding carbon nanotube can also be fabricated.

15      To create a logic device, one or two pentagon-heptagon defects, generated by slightly constricting a metallic nanotube, connected back-to-back and biased properly with external connections, will function as diode or transistor, respectively. The nanotube metallic segments with uniform diameter constitute vertical connectors, and can be connected to the carbon nanotube device by patterned metal lines (Figure 2).

20      A single carbon nanotube segment with one discontinuity, producing two different conducting regions along the nanotube, will constitute a carbon nanotube diode in one embodiment. The carbon nanotube diode is embedded into a substrate and includes integrated source and drain electrodes. The carbon nanotube diode may be grown vertically aligned.

25      The carbon nanotube transistor of one embodiment is a single carbon nanotube segment with two discontinuities, producing three different conducting regions along the nanotube. The carbon nanotube transistor of this embodiment is embedded into a substrate and includes integrated source, drain, and gate electrodes. The transistor may also be grown vertically aligned.

30      Altering the conductivity at many points along the nanotube axis will also allow us to build multiple stacked transistors from each single carbon nanotube of

the array, thus offering a true 3-D architecture. Therefore, a carbon nanotube transistor of another embodiment constitutes two or more carbon nanotube transistors, each with two discontinuities, stacked vertically. The stacked transistor of this invention is embedded into a substrate and includes integrated source, drain, and gate electrodes for each transistor.

A generic logic device of this invention is constructed by the interconnection of a few (typically three) devices in a given layer, or a few stacked devices on a single carbon nanotube. This generic logic device has 3-D architecture.

Advantages provided by various embodiments of the present invention may include flexibility and reproducibility of synthesizing carbon nanotubes which have dimensions and shapes determined by a vertically aligned template, wherein these carbon nanotubes exhibit rectifying behavior. By reproducing a plurality of these carbon nanotubes, it is possible to show the scalability by fabricating hundreds of carbon nanotube devices with similar, if not identical, electrical characteristics. These electrical characteristics may be verified by testing the rectifying behavior of a carbon nanotube device with the help of scanning probe tools by testing two or three points along the carbon nanotube device. The comparison of the results among multiple carbon nanotube devices fabricated within the same processes demonstrates similar, if not identical, electrical characteristics. Thus, a controllable electrochemical process that allows the fabrication of templates with desired dimensions is described. From this template with desired dimensions, carbon nanotube devices may be fabricated with variable diameters along a vertical axis. By synthesizing or fabricating the carbon nanotube molded by the template with a reliable and reproducible process, it is possible to, with a high degree of quality, synthesize crystalline carbon nanotube with reproducible electrical characteristics. These carbon nanotube devices may be interconnected to create and utilize carbon nanotube transistors and other similar devices. These interconnects may comprise carbon nanotube-to-carbon nanotube, or carbon nanotube-to-metal, or carbon nanotube-to-another-like-conducting-material. The electrical or chemical

etching processes may be manipulated so as to produce templates with distributed and desired density patterns of carbon nanotube devices which, when interconnected, may comprise a full working logic device.

5           The electrical properties of carbon nanotubes comprise, among other things, the particularly high conductivity and rectification properties discussed above. It is desirable to fabricate carbon nanotube transistors in an organized manner and interconnect these carbon nanotube transistors with conducting interconnects. It is extremely desirable to have a process designed to fabricate  
10 carbon nanotube molecular electronic devices with both scalability and manufacturability.

          Part of the uniqueness of the present approach is that carbon nanotube transistor fabrication can be scaled to a large number of devices with the same  
15 batch processes. The large scale, low cost approach of the present disclosure provides extremely fast, low power, ultra-high density logic and memory devices which operate at room temperature. There are at least two generations of device architecture that can be based on the approach of this disclosure. The first generation would use a combination of horizontally patterned metal films, fabricated using conventional lithography and integrated vertical structures  
20 consisting of carbon nanotubes. A second generation architecture would be based on etching horizontal holes to provide horizontal interconnection with the help of a horizontal conductive-only carbon nanotube instead of metallic lines.

## 25       **Additional Embodiments**

          In another embodiment of the present invention, horizontally etched templates may be employed to generate horizontal interconnection with the help of horizontal conductive-only carbon nanotubes instead of metallic interconnects. This task can be accomplished with the help of side electrodes, either on the  
30 surface or buried in the layer of silicon and metal film. For example, two electrodes located on a same level that are energized locally may produce a horizontal template. One needs to ensure that etchant can access the silicon that needs to be dissolved. Horizontal carbon nanotube interconnects may also be

used as part of the carbon nanotube electronic device and not only as interconnects.

Alternatively, it is possible to establish direct lateral connections between the nanotubes by sufficiently expanding a conducting nanotube's diameter as to allow them to touch or tunnel electrons, as shown in Figure 8. The electron tunneling connection may also be the basis for a quantum interacting between the nanotubes beyond the interconnect function it provides. Such fundamentally new interconnect approaches would obviate the need for conventional lithographed metallic interconnects or horizontal carbon nanotube interconnects and provide contact-less interconnection. This approach would also enable greatly increased device density.

In another embodiment of the present invention, the desired discontinuity of the template may be achieved by altering the doping concentration profile of the substrate along its depth. The doping profile may be continuous or discontinuous. For example, continuous profile may be produced with the help of ion implantation or thermal diffusion that may achieve the desired dopant profile. Figure 9 illustrates a dopant profile that was achieved with double sided dopant implantation. A discontinuous profile may be achieved by producing a layered structure of substrates with different doping concentrations as shown in Figure 10. Application of continuous current density to both samples during an electrochemical etching will produce template with variable diameter along its length. Those templates will in turn produce variable shaped carbon nanotubes as illustrated in Figures 9 and 10.

In another embodiment of the present invention, a brick-like structure of substrate, where each brick has desired doping concentration, may be used to fabricate multiple templates, each with its own template profile. The discontinuity produced by each brick depends on the level of its doping. Figure 11 illustrates the design of this brick-like structure. Application of continuous current density to such sample during an electrochemical etching will produce a template with a profile that depends on which brick it passes through. The brick-like structure

may be constructed with the help of multi-layer patterning, masking, and dopant implantation.

5 One alternative to using a platinum mesh electrode is to pattern platinum electrodes on the substrate and provide the required current flux on a localized area of the substrate. Platinum is resistant to the HF but other material may be used as electrode especially if it is buried in a layer of silicon. This invention allows that we provide different current to different electrodes and therefore micro-manage the electrochemical process. In this embodiment, individual control of fabricating each template or group of templates may be achieved by producing an individual electrode for each template or group of templates. The electrode will carry the desired current recipe for that template or group of templates. For example, in one area of the sample, we may etch with constant current (Figure 12A,) and in the adjacent area, we may vary the current to produce variable template (Figure 12B). In another example, we may use two electrodes that are laterally off from each other and are vertically separated by a silicon substrate to produce sloped templates with respect to the horizontal substrate, as illustrated in Figure 12C. Alternatively, optical illumination with a pattern matching the pattern of the templates may be used in lieu of the individual electrodes to control the shape of each template or group of templates. The optical pattern may be generated by a lithographic tool.

25 In another embodiment of the present invention individual control of fabricating each template or group of templates can be achieved with the help of masking (Figure 13). Masking is therefore used to micro-manage the electrochemical process. With this method selected areas of the substrate will be masked while other will be exposed. Using this method an individual template or group of templates with desired discontinuities can be fabricated from the exposed areas while the masked areas will remain unprocessed (Figure 13A). In subsequent process steps the pattern of the mask can be changed so that other areas of the substrate can now be processed. Therefore, another individual template or group of templates can be fabricated from the exposed areas with discontinuities different from the first set of fabricated templates (Figure 13B). The

advantage of this approach is that allows selective processing of the substrate, where each area is processed with its own recipe of desired discontinuities. The masking layer needs to be resistant to the etchant.

5           In another embodiment, the material for one or more of the horizontal interconnects may also be a catalyst material. This process allows the metal catalyst to already be present when the template uncovers the layer. In some applications, this may be the most suitable way to provide the catalyst.

10           Although the present invention has been described in detail, it should be understood that various changes, substitutions and alterations can be made hereto without departing from the spirit and scope of the invention as described by the appended claims.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188